

5.6" TFT-LCD Monitor (Stand Type)

Model No : RA-56



FEATURES:

- OSD (On Screen Display) control for: COLOR, TINT, and BRIGHTNESS, CONTRAST and MIRROR (L/R, U/D)
- Wireless IR remote control / Press Button control
- NTSC/PAL signal auto detection
- 2 Video Inputs(the 2nd Input source could be CCD camera for Rear View)

SPECIFICATIONS:

Display:	5.6" active matrix TFT-LCD (4:3)
Back Light:	Built-in CCFT
Dot Format:	960 (H) x 284(V)
Dot Pitch:	0.118mm(H) x 0.362mm(V)
Brightness:	250 cd/m ² (Nit)
Viewing angles:	45/45/10/30 degrees (L/R/T/B)
Pixel configuration:	Stripe
Power requirements:	12 V/ DC.
Video signal:	1V p-p (positive) 75 ohms.
Video system:	NTSC/PAL Auto Detection
Operating temperature:	32-122°F. or 0-50°C

PACKING:

1 SET/WHITE BOX, 6 SETS/CTN/5.2 KGS/6.2 KGS/1.2'



ROCKvision Technology Co., Ltd.

2F-6, No16. Sec 1, Chang-an E,Rd., Taipei City 10442, Taiwan.

Tel: (+886) 2 2523 1120 Fax: (+886) 2 2523 1223

E-mail: sales@rockvision.com.tw