

Quad/Split Screen Monitor

Model Number: RH-70

- ◆ **QUAD / Split display function**
- ◆ **4 cameras input and providing power**
- ◆ **Auto rear view function when reverse**
- ◆ **Power source from DC9.6V to DC32V**
- ◆ **Brightness 400cd/m. Contrast Ratio 300:1**
- ◆ **Provide distant gage when shifting to Reverse gear**
- ◆ **User friendly OSD control by encoder switch**
- ◆ **Adjustable CCD mirror function through OSD**
- ◆ **Day & night auto control by CDS**



Specification:

Screen size	7 inch (diagonal)
Active area	154.08 (H) x 86.58(V)
Pixel configuration	0.107 x 0.370
Resolution	1440(W) x 234(H)
Viewing angle	UP: 60° / Down: 60° / Left: 60° / Right: 60°
Power source	DC9.6V – DC32V
Contrast ratio	12.5007
Brightness	400 cd/m ²
Composite Video In	
Connector	RCA
Input signal	1Vp-p / 75ohm
Camera Mini Din In	
Connector	6 pin mini din
Input video signal level	1 Vp-p / 75 ohm
Input audio signal level	1 Vp-p
Power output for camera	DC 12V / 350 mA
AV Audio in	
Connector	RCA
Input signal level	1 Vp-p / 1K ohm
Composite Video Live out	

Connector	RCA
Input signal level	1Vp-p / 75 ohm
Cam Out	
Connector	RCA
Input signal level	1Vp-p / 75 ohm
Audio Live out	
Connector	RCA
Input signal level	1Vp-p / 1k ohm
Dimension	
W x H x D	192 x 140.5 x 51.8 mm
Weight	N.W.: 2 KGS / G.W.: 2.28 KGS
Environmental	
Operation temperature	-10°C ~ +70°C
Storage temperature	-30°C ~ +80°C
Humidity	20% ~ 80%



2F-6, No16, Sec 1, Chang-an E,Rd., Taipei City 10442, Taiwan.

Tel: (+886) 2 2523 1120 Fax: (+886) 2 2523 1223

E-mail: sales@rockvision.com.tw